

ENDON®

Owen Reader Wall Light Fitting

INSTRUCTION MANUAL

Safety Warnings

- This product is only suitable for connection to a 240V~50Hz supply in accordance with current IEE wiring regulations, and should be installed in accordance with local Building Regulations. They are for domestic, indoor ceiling use only, and are **not** suitable for a Bathroom location.
- The light fitting should be connected to a lighting circuit protected by a 5 amp fuse (or a 6 amp miniature circuit breaker).
- Before installing your light fitting always switch off the mains supply, and remove the appropriate fuse or switch off the appropriate circuit breaker before commencing installation. Ensure that no one else has access that would enable the supply to be inadvertently reconnected.
- **This is a Class I product and must MUST be Earthed.** The terminal blocks are supplied according to requirements of the fitting.
- Never fit bulbs of a higher wattage than those specified on the label (as these may cause overheating and damage the fitting).
- If you are in any doubt about your competence please consult a qualified electrician.
- If any modification is made it will invalidate the warranty and may render the product unsafe.
- This product is dimmable when used with a dimmable bulb.
- The LED of this luminaire is not replaceable; when the light source reaches its end of life the whole luminaire shall be replaced.

Care Information

Allow 10 minutes to cool before replacing, adjusting or cleaning.

Clean with a dry cloth only. Do not use liquid or abrasive cleaners on this product.

Assembly/ User Instructions

Before you start

Please read these instructions carefully before fitting and retain for reference.

Check the packaging and make sure that you have all the required parts.

Follow each assembly step in order to prevent incorrect assembly.

Ensure that the product is fully assembled as illustrated before use.

The Light pack contains:

Light fitting.

Terminal connection block.

Fixing pack, including Allen Key

The following tools may be required:

Selection of cross and flat head screwdrivers.

Electric drill and assorted drill bits.

Wire strippers.

These assembly diagrams overleaf are intended as a guide – if in doubt consult a qualified electrician.

1. Decide on the position of the light fitting, or remove existing light fitting. Take a note of the position of the electrical connections. Ensure there is a solid mounting surface.
2. Using the supplied hex key (A), remove the two side hex screws (B) and retain them for re-use. Use the fixing bracket (C) as a template to mark the screw holes, and secure to the wall with appropriate screw fixings (D), making sure the bracket is correctly aligned.
3. Support your fitting and connect the house wiring to the terminal block (E) – see expanded wiring details overleaf.
4. Secure the wall cup over the bracket by using the screws (B) removed in Point 2. Ensure the wall cup is correctly oriented with the lampholder facing upwards.



Assembly/ User Instructions Continued

- Secure the shade (not supplied) (F) with the shade ring (G).
- Fit the bulb (H - not supplied). **NOTE: Never fit bulbs of a higher wattage than those specified on the label (as these may cause overheating and damage the fitting).**
- Turn on the power and test. Switch on with the toggle switches. The left-hand switch (I) operated the E27 bulb and the right-hand switch (J) operates the LED reading light. **Do not stare directly at the LED beam.**

